



# APC Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Brand : APC

Product code: SRT2200XLI

**Product name :** Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

APC Smart-UPS On-Line, 2200VA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit. UPS topology: Double-conversion (Online), Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 367 VAh, Typical backup time at full load: 3.9 min. Form factor: Rackmount/Tower, Product colour: Black, Cable length: 2.44 m. Width: 85 mm, Depth: 584 mm, Height: 432 mm




Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	2.2 kVA	<b>Design</b>	
Output power *	1980 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Cable length	2.44 m
Input operation voltage (min) *	100 V	Product colour *	Black
Input operation voltage (max) *	275 V	Display type	LCD
Input frequency *	40/70 Hz	LED indicators	✓
Output operation voltage (min)	220 V	International Protection (IP) code	IP20
Output operation voltage (max)	240 V	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Output frequency	50/60 Hz	<b>Operational conditions</b>	
Surge energy rating	340 J	Operating temperature (T-T)	0 - 40 °C
Efficiency	92.2%	Storage temperature (T-T)	-15 - 45 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	<b>Technical details</b>	
Web-based management	✓	Sustainability certificates	ENERGY STAR, Green Premium
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces		<b>Weight &amp; dimensions</b>	
AC outlet types	C13 coupler, C19 coupler	Width	85 mm
Power plug	C20 coupler		
AC outlets quantity	10 AC outlet(s)		
Number of output IEC jumpers	2		

Ports & interfaces		Weight & dimensions	
USB port	✓	Depth	584 mm
Serial interface	✓	Height	432 mm
Serial interface type	RJ-45	Weight	25 kg
SmartSlot	✓	Package width	599 mm
Battery		Package depth	810 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery capacity	367 VAh	Package weight	30.8 kg
Number of batteries supported	1	Packaging data	
Typical backup time at full load	3.9 min	Bracket	✓
Typical backup time at half load	11.6 min	Cables included	USB cable
Battery life (max)	5 year(s)	Quick installation guide	✓
Battery recharge time	3 h	Warranty card	✓
Hot-swap battery	✓	Software CD	✓
Automatic battery test	✓	Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Interface	SmartSlot
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Packaging content	Power cord Removable support feet



0731304317630



731304317630

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.