



APC Smart-UPS On-Line, 3kVA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Brand : APC

Product code: SRT3000XLI


Product name : Smart-UPS On-Line, 3kVA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Smart-UPS On-Line, 3kVA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

APC Smart-UPS On-Line, 3kVA, Tower, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/O rail kit. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 505 VAh, Typical backup time at full load: 4 min. Form factor: Tower, Product colour: Black, Cable length: 2.44 m. Width: 85 mm, Depth: 635 mm, Height: 432 mm



Runtime Graph




Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	3 kVA	Cold start	✓
Output power *	2700 W	Design	
Waveform *	Sine		
Input operation voltage (min) *	100 V	Form factor *	Tower
Input operation voltage (max) *	275 V	Cable length	2.44 m
Input frequency *	40/70 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	International Protection (IP) code	IP20
Output frequency regulation	50/60 Hz	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Surge energy rating	340 J	Operational conditions	
Efficiency	93.5%		
Crest factor	3:1	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-15 - 45 °C
Noise level	55 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Web-based management	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	Technical details	
Ports & interfaces			
Sustainability certificates	ENERGY STAR, Green Premium	Compliance certificates	RoHS
AC outlet types		Weight & dimensions	
Power plug	C20 coupler	Width	85 mm
AC outlets quantity	10 AC outlet(s)	Depth	635 mm
Number of output IEC jumpers	2	Height	432 mm
USB port	✓	Weight	31.3 kg
Serial interface	✓	Package width	599 mm
Serial interface type	RJ-45	Package depth	871 mm
SmartSlot	✓	Package height	246 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	36.7 kg
Battery capacity	505 VAh	Packaging data	
Number of batteries supported	1	Rack mount kit	✓
Typical backup time at full load	4 min	Bracket	✓
Typical backup time at half load	11.8 min	Cables included	USB cable
Battery life (max)	5 year(s)	Quick installation guide	✓
Battery recharge time	3 h	Warranty card	✓
Hot-swap battery	✓	Software CD	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V
		Packaging content	Country-specific detachable power cord Removable support feet



0731304317678



731304317678

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.