

- Outer Jacket: White   
  Aluminium Foil   
  Separator/Spline   
  Copper-Clad Aluminium (CCA)
- Outer Jacket: Grey   
  Braiding   
  Pull-Box   
  Solid Copper
- Outer Jacket: Black   
  Drain wire   
  Cable roll

### Construction & Dimensions

<b>Conductor</b>	<b>Material</b>	SC (Solid / Bare Copper)
	<b>Size</b>	24 AWG (4 pairs)
	<b>Construction</b>	1 / 0.50mm ± 0.008mm
	<b>Resistance</b>	≤ 9.5 Ω / 100M at 20°C
<b>Insulation</b>	<b>Material</b>	PE
	<b>Avg. Thickness</b>	0.20mm
	<b>Min. Thickness</b>	0.19mm
	<b>Diameter</b>	0.91 ± 0.03 mm
	<b>Resistance</b>	Min.5000 mega-Ω / km at 20°C
	<b>Dielectric Test</b>	1000V DC/1min; No Breakdown
<b>Inner Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	25mm Underneath
<b>Outside Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	150mm Underneath
<b>Jacket</b>	<b>Material</b>	PVC
	<b>Avg. Thickness</b>	0.55mm
	<b>Min. Thickness</b>	0.50mm
	<b>Diameter</b>	5.1 ± 0.30mm
<b>Other</b>	<b>Install Temp</b>	-20°C ~ +60°C