

- Outer Jacket: White
- Aluminium Foil
- Separator/Spline
- Copper-Clad Aluminium (CCA)
- Outer Jacket: Grey
- Braiding
- Pull-Box
- Solid Copper
- Outer Jacket: Black
- Drain wire
- Cable roll

### Construction & Dimensions

<b>Conductor</b>	<b>Material</b>	CCA (Copper-clad aluminium)
	<b>Size</b>	23 AWG
	<b>Construction</b>	1 / 0.56mm ± 0.01mm
	<b>Resistance</b>	≤ 19.5 Ω / 100M at 20°C
<b>Insulation</b>	<b>Material</b>	HDPE
	<b>Avg. Thickness</b>	0.20mm
	<b>Min. Thickness</b>	0.19mm
	<b>Diameter</b>	0.95 ± 0.03 mm
	<b>Resistance</b>	Min.5000 mega-Ω / km at 20°C
	<b>Dielectric Test</b>	1000V DC/1min; No Breakdown
<b>Inner Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	25mm Underneath
<b>Outside Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	200mm Underneath
<b>Separator/Spline</b>	<b>Material</b>	Polyethylene
	<b>Construction</b>	4.0 x 4.0 x 0.4mm
<b>Shielding</b>	<b>Material</b>	Mylar
	<b>Coverage</b>	100% coverage with 25% overlapping
	<b>Drain Wire</b>	1 / 0.4mm CCA
	<b>Material</b>	Aluminium / Mylar
	<b>Coverage</b>	100% coverage with 25% overlapping face inside
	<b>Material</b>	Aluminium magnesium wire
	<b>Construction</b>	64 * 0.12 AL
<b>Jacket</b>	<b>Material</b>	PVC
	<b>Avg. Thickness</b>	0.55mm
	<b>Min. Thickness</b>	0.50mm
	<b>Diameter</b>	6.4 ± 0.15mm
<b>Other</b>	<b>Install Temp.</b>	-20°C ~ +60°C