

- Outer Jacket: White   
  Aluminium Foil   
  Separator/Spline   
  Copper-Clad Aluminium (CCA)
- Outer Jacket: Grey   
  Braiding   
  Pull-Box   
  Solid Copper (SC)
- Outer Jacket: Black   
  Drain wire   
  Cable roll

Construction & Dimensions		
<b>Conductor</b>	<b>Material</b>	CCA (Copper-clad aluminium)
	<b>Size</b>	23 AWG (4 pairs)
	<b>Construction</b>	1 / 0.56mm ± 0.01mm
<b>Insulation</b>	<b>Material</b>	HDPE
	<b>Avg. Thickness</b>	0.21mm
	<b>Min. Thickness</b>	0.19mm
	<b>Diameter</b>	0.95 ± 0.03 mm
	<b>Resistance</b>	Min.5000 mega-Ω / km at 20°C
	<b>Dielectric Test</b>	1000V DC/1min; No Breakdown
<b>Inner Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	30mm Underneath
<b>Outside Layer</b>	<b>Direction</b>	S
	<b>Pitch</b>	200mm Underneath
<b>Separator/Spline</b>	<b>Material</b>	Polyethylene
	<b>Construction</b>	4.0 x 4.0 x 0.4mm
<b>Jacket</b>	<b>Material</b>	PVC
	<b>Avg. Thickness</b>	0.58mm
	<b>Min. Thickness</b>	0.55mm
	<b>Diameter</b>	6.0 ± 0.20mm
<b>Other</b>	<b>Install Temp.</b>	20°C ~ +60°C