

- Outer Jacket: White   
  Aluminium Foil   
  Separator/Spline   
  Copper-Clad Aluminium (CCA)
- Outer Jacket: Grey   
  Braiding   
  Pull-Box   
  Solid Copper (SC)
- Outer Jacket: Black   
  Drain wire   
  Cable roll

Construction & Dimensions		
Conductor	Material	CCA (Copper-clad aluminium)
	Size	23 AWG (4 pairs)
	Construction	1 / 0.56mm ± 0.01mm
	Resistance	≤ 9.5 Ω / 100M at 20°C
Insulation	Material	HDPE
	Avg. Thickness	0.20mm
	Min. Thickness	0.19mm
	Diameter	0.95 ± 0.03 mm
	Resistance	Min.5000 mega-Ω / km at 20°C
	Dielectric Test	1000V DC/1min; No Breakdown
Inner Layer	Direction	S
	Pitch	25mm Underneath
Outside Layer	Direction	S
	Pitch	200mm Underneath
Separator/Spline	Material	Polyethylene
	Construction	4.0 x 4.0 x 0.4mm
Shielding	Material	Mylar
	Coverage	100% coverage with 25% overlapping
	Drain Wire	1 / 0.4mm CCA
	Material	Aluminium / Mylar
	Coverage	100% coverage with 25% overlapping face inside
	Material	Aluminium magnesium wire
	Construction	64 * 0.12 AL
Inner Jacket	Material	PVC
	Avg. Thickness	0.50mm
	Min. Thickness	0.45mm
	Diameter	6.4 ± 0.15mm
Outer Jacket	Material	LDPE
	Avg. Thickness	0.55mm
	Min. Thickness	0.50mm
	Diameter	7.6 ± 0.15mm