


Li-FePO4 Battery

LFP12-7HD (12.8V - 7Ah)

Physical Dimensions



Electrical Characteristics	Nominal Voltage	12.8V
	Nominal Capacity	7Ah
	Energy	89.6Wh
	Internal Resistance	≤180mΩ
	Cycle Life	>2000 cycles at 0.2C 90% DOD
	Months Self Discharge	<3%
Charge	Charge Voltage	14.4+/-0.2V
	Charge Mode	CC at 0.2C to 14.4V, CV14.6V stop current = 0.02C
	Charge Current	1.4A
	Max. Charge Current	6A (Max)
Discharge	Max. Continuous Current	15A
	Max. Pulse Current	35A (3s)
	Discharge cut-off Voltage	8V
Environment	Charge Temperature	0°C to 45°C at 60±25% Relative Humidity
	Discharge Temperature	- 20°C to 60°C at 60±25% Relative Humidity
	Storage Temperature	0°C to 40°C 60±25% Relative Humidity
	Ingress Protection	IP56
Mechanical	Cell Material	LiFePO4
	Plastic Case Material	ABS
	Dimensions (mm)	151*65*99mm
	Weight (Kg)	1.1KG
	Terminal	T1
BMS	Protection Function	Over charge, Over discharge, Over current, Short Circuit, Cell Balancing function, Temperature protection

Discharge Characteristics

