



## **UB-UVC-G5-DOME**

### Overview

Dimensions : Ø109.2 x 64.5 mm  
(Ø4.3 x 2.5")

IR Night Vision : 9 m (30 ft)

Resolution : 2K

Field of View : H: 102.4°, V: 54.9°, D: 120.6°

Audio : Two-way audio

Weatherproofing : IPX4 (While Covered)

Tamper Resistance : IK08

Mounting : Wall, ceiling mount (Included)

Junction box, arm mount (Optional)

### Performance

Networking Interface : 10/100 MbE RJ45 port

Image Settings : Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

Max. Frame Rate : 30 FPS

Resolution : 4MP 2688 x 1512 (16:9)

Sensor : 5MP CMOS

Lens : Fixed focal length

Night Mode : Built-in IR LED illumination and IR cut filter



## **UB-UVC-G5-DOME**

### Hardware

Max. Power Consumption : 5W

Supported Voltage Range : 37–57V DC

Power Method : PoE

Processor : Dual-core Arm® Cortex®-A7 based chip

Weight : Without mount: 370 g (13.1 oz)

With mount: 390 g (13.8 oz)

Enclosure Material : Aluminum alloy, polycarbonate, hard-coated dome

Mount Material : Polycarbonate, stainless steel

Button : (1) Factory-reset

Ambient Operating Temperature : -20 to 40° C (-4 to 104° F)

Ambient Operating Humidity : 0 to 90% noncondensing

Certifications : CE, FCC, IC