

UniFi

Flex 10GbE Datasheet

MiRO

Switch Flex 10GbE SKU: UB-USW-FLEX-XG



A compact, 5-port, Layer 2 switch that supports 10 GbE speeds and can be powered with PoE or a 5V USB-C adapter. 4 × 10 GbE ports and 1 x GbE PoE+ input port for power

Switch Flex 10GbE

SKU: UB-USW-FLEX-XG

Mechanical

Dimensions	135 x 185 x 32 mm (5.3 x 7.3 x 1.3")
Weight	1.2 kg (2.7 lb)
Enclosure material	Polycarbonate

Hardware

Management interface	Ethernet In-Band
Networking interface	(1) GbE, PoE+ RJ45 port (4) 10 GbE RJ45 ports
Total non-blocking throughput	41 Gbps
Switching capacity	82 Gbps
Forwarding rate	61.012 Mpps
Power method	(1) PoE+, 50—57V DC, 25W (1) USB Type-C, 5V DC, 5A
Power supply	PoE+ (Pins 1, 2+/3, 6- or 4, 5+/7, 8-) AC/DC power adapter, 5V DC, 5A, 1.5 m cord (Included)
Supported voltage range	90—264V AC (Adapter)
Max. power consumption	25W
ESD/EMP protection	Air: ± 16kV, contact: ± 12kV
Button	Factory reset
Operating temperature	-5 to 45° C (23 to 113° F)
Operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

LEDs

System	Status
Ethernet	Speed/link/activity

Application Requirements

UniFi Network	Version 6.1.67 and later
---------------	--------------------------

Switch Flex 10GbE SKU: UB-USW-FLEX-XG

