




55 inch LED Backlight SMART DISPLAY SPEC.

Customer Model Name

55S98U



1.Panel spec

Size	54.64" diagonal
Backlight	DLED direct Type
Maximum resolution	3840×2160
LCM Center Luminance of White	1200:1
Contrast ratio (Typ)	9ms
Response time(Typ)	16:09
Display scale	Typ(H:176°, V:176°)
Viewing angle(CR>10)	1.07 B
Display Colors	≥NTSC 62%.
Color Gamut(NTSC)	Min:250cd/m2;Typ:300cd/m2
Local dimming	nonsupport
Uniformity of Luminance	≥65%.

2.Hardware Information

CPU Frame	ARM Cortex-A53/1.5GHz/Quad core
GPU	G52MP2/Dual core
RAM(DDR3)	1.5GB
ROM(Flash)	8GB (16GB optional)
Audio power(Output)	8W+8W
WiFi(Type)	2T2R, 2.4GHz (IEEE 802.11b/g/n)
HDMI 2.0 (HDCP 2.2)	3
USB 2.0	2
AV In	1
RJ-45	1
Audio Out	1
SPDIF Out	1

3.Software Function

MTS/NICAM	MTS
Sleep time setting	YES
Teletext	YES
PVR	YES
EPG	YES
CC(Closed caption)	NO
AD(Audio description)	YES
TTS(Text to Speech)	NO
DOLBY	YES
HDMI-ARC	HDMI-1
HDMI-CEC	YES
HDMI-MHL	NO
Operation system	Android 9.0
OTA	YES
Hotel mode	Optional
Local dimming	NO

4.Structure Information

Base model name	BCCI-55 I shaped metal stand
Size (without stand) L×W×H	1228x73x711mm
Size (with stand) L×W×H	1228x243x742mm
Size (carton) L×W×H	1346x124x806mm
Net Weight (without stand)	12.5kg
Net Weight (with stand)	12.7kg
Gross Weight (without stand)	16.0kg
Gross Weight (with stand)	16.2kg
Size (Wall hanging)	300x200mm

5.Power Management&Safety&Certificate

Power input	100-240VAc
Fire rating	UL94-HB75
Standby power	≤0.5W
Rated power	130W
Working condition	Temperature:5℃~40℃, Humidity:10~80, Atmosphere:86kPa~106kPa
Storage condition	Temperature:-20℃~55℃, Humidity:10~80, Atmosphere:86kPa~106kPa

6.Accessory

Stand(Optional)	1PCS
Remote control	1PCS
Instruction	1PCS
Battery	2PCS