

SKU: UB-UAP-U7-PRO



The U7 Pro is a ceiling-mounted Wi-Fi 7 Access Point with 6 spatial streams and 6GHz support for interference-free Wi-Fi in demanding, large-scale environments. Supports up to 300+ connected devices, powered using PoE+ and 2.5GbE uplink.

UniFi | Wi-Fi Access Point Datasheet

MiRO

U7 Pro

SKU: UB-UAP-U7-PRO

Mechanical

Dimensions	Ø206 x 46 mm (Ø8.1 x 1.8")
Weight	680 g (1.5 lb)
Enclosure material	Polycarbonate, metal
Mount material	Stainless steel (SUS304), galvanized steel (SGCC)

Hardware

Networking interface	(1) 1/2.5 GbE RJ45 port
Management interface	Ethernet
Power method	PoE+
Power supply	UniFi PoE switch
Supported voltage range	44—57V DC
Max. power consumption	21W
Max. TX power	
2.4 GHz	22 dBm
5 GHz	26 dBm
6 GHz	23 dBm

MIMO

2.4 GHz	2 x 2
5 GHz	2 x 2
6 GHz	2 x 2

Throughput rate

2.4 GHz	688 Mbps
5 GHz	2822 Mbps
6 GHz	5765 Mbps

Antenna gain

2.4 GHz	4dBi
5 GHz	6 dBi
6 GHz	5.8dBi

LEDs	White/blue
Button	Factory reset
Mounting	Wall/ceiling (Included)
Operating temperature	-30 to 60° C (-22 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

UniFi | Wi-Fi Access Point Datasheet

MiRO

U7 Pro

SKU: UB-UAP-U7-PRO

Software

WiFi standards	802.11a/b/g/n/ac/ax/be
Wireless security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3/PPSK)
BSSID	8 per radio
VLAN	802.1Q
Advanced QoS	Per-user rate limiting
Guest traffic isolation	Supported
Concurrent clients	300+

Supported Data Rates

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160)
802.11ax (WiFi 6)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)
802.11be (WiFi 7)	7.3 Mbps to 5.7 Gbps (MCS0 - MCS13 NSS1/2, EHT 20/40/80/160/240/320)

Application Requirements

UniFi Network	Version 8.0.26 and later
UniFi OS	Version 3.2 and later

U7 Pro

SKU: UB-UAP-U7-PRO

